

INSTALLATION INSTRUCTIONS

MAVERICK AMBI SAFETY FOR AR-15

PART NUMBER
MA-37400

Warning: Always verify your rifle is unloaded prior to installing any parts!

The Maverick Stribog Safety is compatible with all Models of Grand Power Stribog.

The following is included in the kit:

- 1x Stribog 90 Degree Safety shaft
- 2x Screws
- 1x Allen wrench
- 9x Safety levers of various sizes

You will need the following tools:

- Small flatblade screwdriver
- Dental pick

STEP 1:

Remove the magazine from the rifle, pull back on the charging handle and ensure the chamber is clear of live ammunition. Let the charging handle go to the forward position and place the rifle on "SAFE".

STEP 2:

Remove the lower receiver from the upper. Cock the hammer, place the safety levers at a 45 degree angle midway between "Safe" and "Fire" The OEM safety levers are two parts- a left and a right, each retained by their own "maple leaf" shaped detent with spring. Press down on the visible edge of the detent on the left side of the inner receiver pocket, and slowly pry the left side lever out of the lower. Repeat with the right side safety lever. Take care not to drop or lose the "maple leaf" safety detents or springs.

STEP 3:

Remove the left side "maple leaf" detent and spring, you may need a dental pick to pull the spring out of its hole. Store both parts in a safe place.

STEP 4:

Mount the preferred safety lever on the left side of the safety shaft. The left side of the shaft has a ridge on it, and the right side has two horizontal cuts on the underside of it where the detent engages.

STEP 5:

Feed the safety shaft through the left side of the receiver, press down the "maple leaf" detent and spring on the right side, and continue to feed through right side hole. Use your hand to press the fire control cage down, as it has a tendency to try and spring up when the safety lever is out of the gun.



STEP 6:

Mount the preferred safety on the right side of the safety shaft, cock the hammer if not already cocked, set on Safe, and pull the trigger and ensure the hammer does not drop. Set on Fire, use your thumb to catch the hammer, and pull the trigger to ensure the hammer drops. If it functions correctly, reassemble the firearm.

PERFORM A FUNCTION CHECK PER THE FIREARM INSTRUCTION MANUAL TO VERIFY CORRECT OPERATION.

YOUR MAVERICK SAFETY IS NOW INSTALLED!



Visit www.youtube.com/manticorearms
to view videos on the installation and
use of this product!

Manticore Arms, Inc.

7300 Peppermill Parkway, North Charleston, SC 29418



854-444-6209



Info@Manticorearms.com

**MADE
IN USA**



MANTICOREARMS.COM