




MANTICORE ARMS, INC.

MADE IN



TAVOR 7 ENHANCED PORT COVER INSTALLATION INSTRUCTIONS

Warning: Always verify your rifle is unloaded prior to installing any parts!

The Tavor 7 Enhanced Port Cover is compatible with the following firearms:

IWI Tavor 7 (Tavor SAR 7.62 NATO caliber)

The following is included in the kit:

- (1) Port Cover
- (2) Locking Nuts
- (2) 8-32 x 7/16" flat head screws
- (1) 3/32" allen wrench



You will need the following tools:
Flathead screwdriver

STEP 1:

Remove Bolt Carrier Group from the firearm

STEP 2:

On the side you plan to install the Tavor 7 Enhanced Port Cover, slide the cover half open. Use the flathead screwdriver to press down and rotate the screw in the center of the plastic brass deflector 90 degrees. Release pressure and the screw, a spring, and the brass deflector will come off the sheet metal port cover. Store the removed parts in a plastic baggie in the stock.



STEP 3:

Slide the OEM sheet metal port cover back into the stock so the port is fully open. (If you need to use the OEM sheet metal port cover in the future, point the firearm muzzle down on a carpeted surface and tap it several times on the carpet. The sheet metal cover will slide out and be accessible)

STEP 4:

There are grooves in the top and bottom of the receiver that the OEM sheet metal cover slides in. Take one of the Locking Nuts with the circular tower facing the outside of the firearm and locate the "blades" so they are ready to fit in the grooves. (NOTE: the "blades" are larger in one dimension than the other- this is so you can position it in the opening with the smaller dimension, and then rotate it so the larger dimension fits into the grooves.) Rotate clockwise 90 degrees until the "blades" engage in the top and bottom groove in the receiver. Repeat with the second Locking Nut.



STEP 5:

Place the Port Cover over the port with the circle cutout towards the front and larger cutouts to the rear. Slide the Locking nuts as necessary to get them to line up with the screw holes. Insert the screws and tighten with the 3/32" allen wrench down until hand snug. Your Tavor 7 Enhanced Port Cover is now installed!



**SCAN THE QR CODE TO VISIT OUR YOUTUBE CHANNEL
WITH INSTRUCTIONS, ETC.**



WWW.MANTICOREARMS.COM

Manticore Arms, Inc.

7300 Peppermill Parkway
North Charleston, SC 29418

Phone: 854-444-6209

Email: Info@ManticoreArms.com

Revised: 10/07/2024

www.ManticoreArms.com